

EnduroShield™ Tiles & Grout

Do I need to use the steel wool if I have new tiles?

No, only if you have existing tiles. The steel wool is used to remove the build-up of soap scum mineral deposits and lime scaling.

Does the coating get attacked by chemicals?

No. The only way to remove the coating is by using a rough, gritty or abrasive cleaner.

Will the surface become patchy if the coating is worn off in any way?

No. The coating is only two molecules thick and transparent, thus it does not change the appearance of the surface. If an abrasive was to be used, it would not be visible where it was worn away. That area would, however, be harder to clean. The unprotected surface can be easily repaired by cleaning the area and re-spraying with EnduroShield. The molecules will bond directly to the untreated surface.

Do I need to mask the area when I coat the area?

No, the product is not corrosive and will not harm fixtures and fittings. If the product does come in contact, the fixtures or fitting will become water repellent for a short period of time until it wears off.

Do I still need to seal the tiles after I apply this product?

No, the coating not only creates an easy to clean surface, but a permanent protective barrier to resist staining.

Can I apply the product over tiles that have already been sealed with a product?

No, the product needs to be applied untreated tiles and grout to bond with the surface.

If I apply to my toilet, can the coating remain underwater?

Yes, it can. The molecules are permanently bonded, and are impervious to water.

Will a toilet brush remove the coating if applied to a toilet?

No. The bristles on a toilet brush are not strong enough to scratch the surface.